

Application No. 10/801,690

In the specification:

BEST AVAILABLE COPY

Page 3, first paragraph, kindly amend as follows:

Fig. 2 is a simplified illustration of a bottom portion of the magazine of Fig. 1; and
Fig. 3 is a simplified illustration of the magazine of Fig. 1 inserted in a weapon.

Page 3, third paragraph, kindly amend as follows:

The weapons magazine 10 may include a magazine body 12 adapted for storing any number of rounds 14 therein. A biasing device 16, such as a coil spring that cooperates with a pusher element 18, may be provided for urging the rounds 14 out of the magazine body 12, as is well known in the art. The magazine body 12 is adapted to be inserted in a magazine well 50 of a weapon 52 (~~not shown~~Fig. 3), such as but not limited to, a handgun, having a firing axis 54 (~~not shown, but pointing in or out of the plane of the drawing sheet~~Fig. 3).

Page 4, first paragraph, kindly amend as follows:

Unlike the prior art, the light 26 is not necessarily directed in the aiming direction of the weapon. In accordance with a non-limiting embodiment of the present invention, the light 26 is arranged to point in the direction of a longitudinal axis 32 of the magazine body 12, which is not parallel to the firing axis 54 of the weapon 52 (~~again, not shown, but pointing in or out of the plane of the drawing sheet~~Fig. 3). Additionally or alternatively, the light 26 may be flexibly mounted (e.g., as on a flexible fiber optic cable, or on a plate 56 mounted to the rest of the magazine body 12 with a flexible cable or cord 58 and the like), or pivotally mounted (e.g., as on an arm 60 pivotally mounted to the rest of the magazine body 12 with a pinned joint or bearing 62), so that the light 26 may be pointed in any desired direction (Fig. 3).